

Declaration of Performance No Dop-CPR- SORBERG STRONG/1



- 1. Unique identification code of the product-type:
 - SORBERG STRONG
- 2. Inended uses:
 - For use as vapour permeable underlayment for roofing and as wind insulation.
- 3. Manufacturer:
 - SORBERG s.c.
 - ul. Krasickiego 1A/35, 99-200 Poddębice, Polska
- 4. System of assessment and verification of constancy of performance of the construction product:
 - System 3
- 5. Harmonised standard:
 - PN-EN 13859-1:2010
 - PN-EN 13859-2:2010
 - Notified Body no. 1434 Polskie Centrum Badań i Certyfikacji S.A.



6. Declared performances:

	Essential characteristics	Functional	Unit	Harmonized
Reaction to fire		Class E	-	
Resistance to water penetration		Class W1	-	
Tensile strength in longitudinal direction		240 (+40; -50)	N/50mm	
Tensile strength in transverse direction		140 (+35;-35)	N/50mm	PN-EN 13859-1:2010
Elongation in longitudinal direction		60 (+15;-15)	%	PN-EN 13859-2:2010
Elongation in transverse direction		90 (+30;-20)	%	
Tear resistance in longitudinal direction		170 (+40;-40)	N	
Tear resistance in transverse direction		170 (+40;-40)	N	
Flexibility at low temperatures		-30	°C	
After artificial ageing	Resistance to water penetration	Class W1	-	
	Tensile strength in longitudinal	170 (+30;-35)	N/50mm	
	Tensile strength in transverse direction	100 (+25;-25)	N/50mm	
	Elongation in longitudinal direction	40 (+10;-10)	%	
	Elongation in transverse direction	60 (+20;-15)	%	
Dangerous substances		NPD	-	

7. The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Poddębice, 30.01.2017

Krystyna Iwańska

SORBERG S.C.
ul. Krasickiego 1A/35,99-200 Poddębice
NIP 8281414191 REGON 363084464

Krystynu Ywaisha